



AUTOMOTIVE BATTERY FITMENT GUIDE



Thanks for choosing Battery Group Ltd for your battery requirements.

Although we recommend that your new battery is fitted by an approved garage/mechanic we have listed below a step by step guide if you wish to do the job yourself.

1. Wear protective glasses when fitting the battery. Avoid contact with any battery acid.
2. First remove the ground cable. This safely prevents a short circuit between the positive terminal and the vehicle body.
3. Check the battery compartment for corrosion. Thoroughly inspect the brackets for rust and damage. Clean the battery compartment and repair as necessary. Corrosion in the area of the battery can indicate leaked battery acid, in this case consult a workshop to investigate.
4. Remove surface rust and dirt from the battery terminal clamps, as this causes increased contact resistance and therefore considerable malfunctions or premature battery failure.
5. Take care that the terminal clamps are firmly fitted in order to eliminate contact interruptions due to vibrations. When connecting the terminal clamps, care must also be taken that the battery terminals are not damaged by torsion or other mechanical stresses.
6. Take care that the battery is properly seated on installation. Tighten the clamps with a torque wrench. The correct torque can be found in the vehicle manual. Before connection, check the correct polarity of the cables again. First connect the red cable to the positive terminal and then connect the black ground cable to the negative terminal.

Electrical systems in the car might require recalibration after fitment such as sensors and other comfort functions. If this is the case it is advised that this be done by a professional.

Need a charger for your new battery? Contact our team for advice on 01226 885050.



IMPORTANT!

Please remove immediately the transport bungs after receiving the battery. These can be found on both sides of the battery.

Since there is acid in the battery and the battery may have increased in pressure during transport. Please remove the bungs **away from the body**.



For more information on battery use and maintenance please visit our website:

www.batterygroup.co.uk

*Failure to remove the bungs will cause the battery to swell and expand invalidating your warranty

HOW DID WE DO TODAY?

Leave a review for Battery Group on Facebook, Trustpilot or Google.

If you're not happy, please contact us, so we can rectify this.



VISIT OUR WEBSITE FOR THE WIDEST RANGE OF DISCOUNTS ON PREMIUM BRANDS



Panasonic **EXIDE** **DURACELL** **VARTA** **ULTRALIFE**



www.batterygroup.co.uk