

Page 1 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.04.2022 / 0017 Replacing version dated / version: 25.01.2022 / 0016 Valid from: 01.04.2022 PDF print date: 23.05.2022 Marine 2T Motor Oil

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

## **1.1 Product identifier**

ആ

# Marine 2T Motor Oil

**1.2** Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Two-stroke motor oil Uses advised against: No information available at present.

## 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

# 1.4 Emergency telephone number

Emergency information services / official advisory body:

## Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR) +1 872 5888271 (LMR)

**SECTION 2: Hazards identification** 

# 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

## 2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP) Not applicable

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

## **SECTION 3: Composition/information on ingredients**

## 3.1 Substances

n.a.



Page 2 of 13

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.04.2022 / 0017 Replacing version dated / version: 25.01.2022 / 0016 Valid from: 01.04.2022 PDF print date: 23.05.2022 Marine 2T Motor Oil

## 3.2 Mixtures

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119456620-43-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	926-141-6
CAS	
content %	10-<25
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066
	Asp. Tox. 1, H304
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	
Registration number (REACH)	01-2119474889-13-XXXX
Index	649-483-00-5

Index	649-483-00-5
EINECS, ELINCS, NLP, REACH-IT List-No.	276-738-4
CAS	72623-87-1
content %	1-<3
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Asp. Tox. 1, H304

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Remove person from danger area.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

## Eye contact

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Keep Data Sheet available.

## Ingestion

Do not induce vomiting. Consult doctor immediately. Danger of aspiration.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. The following may occur:

Drying of the skin.

Irritation of the skin.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

## SECTION 5: Firefighting measures

#### 5.1 Extinguishing media Suitable extinguishing media CO2 Foam Dry extinguisher

Unsuitable extinguishing media

High volume water jet



Page 3 of 13

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.04.2022 / 0017 Replacing version dated / version: 25.01.2022 / 0016 Valid from: 01.04.2022 PDF print date: 23.05.2022 Marine 2T Motor Oil

## 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Oxides of nitrogen Flammable vapour/air mixtures

## 5.3 Advice for firefighters

For personal protective equipment see Section 8. Protective respirator with independent air supply. According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

## **SECTION 6:** Accidental release measures

# 6.1 Personal precautions, protective equipment and emergency procedures

#### 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

#### **6.1.2 For emergency responders**

See section 8 for suitable protective equipment and material specifications.

#### 6.2 Environmental precautions

#### If leakage occurs, dam up.

Resolve leaks if this possible without risk. Prevent from entering drainage system.

## 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

## 7.1 Precautions for safe handling

## 7.1.1 General recommendations

Observe directions on label and instructions for use.

Take measures against electrostatic charging, if appropriate.

If applicable:

Use explosion-proof equipment.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

## 7.2 Conditions for safe storage, including any incompatibilities

#### Not to be stored in gangways or stair wells.

Store product closed and only in original packing. Protect against moisture and store closed.

## 7.3 Specific end use(s)

No information available at present.

## **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters



	Page 4 of 13
	Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
	Revision date / version: 01.04.2022 / 0017
	Replacing version dated / version: 25.01.2022 / 0016
	Valid from: 01.04.2022
	PDF print date: 23.05.2022
	Marine 2T Motor Oil
_	

GB

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 1200 mg/m3

Chemical Name	Hydrocarbons, C1	1-C14, n-alkanes, isoalkanes, cycli	cs, <2% aromatics	
WEL-TWA: 1200 mg/m3 (>=C7 no	ormal and branched	WEL-STEL:		
chain alkanes)				
Monitoring procedures:	-	Draeger - Hydrocarbons 0,1%/c (81	03 571)	
	-	Draeger - Hydrocarbons 2/a (81 03	581)	
		Compur - KITA-187 S (551 174)	,	
BMGV:			Other information:	
Chemical Name	Oil mist, mineral			
WEL-TWA: 5 mg/m3 (Mineral oil,	excluding metal	WEL-STEL:		
working fluids, ACGIH)				
Monitoring procedures:	-	Draeger - Oil Mist 1/a (67 33 031)		
BMGV:			Other information:	

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based									
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note			
	Environmental								
	compartment								
	Human - oral		PNEC	9,33	mg/kg feed				
Consumer	Human - inhalation	Long term, local effects	DNEL	1,2	mg/m3	24h			
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,4	mg/m3	8h			

Distillates (petroleum), hydrotreated heavy paraffinic									
Area of application Exposure route / Effect on health Descriptor Value Unit Note									
	Environmental		-						
	compartment								
	Environment - oral (animal		PNEC	9,33	mg/kg feed				
	feed)								

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE).
(11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit

value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

## 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.



Page 5 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.04.2022 / 0017 Replacing version dated / version: 25.01.2022 / 0016 Valid from: 01.04.2022 PDF print date: 23.05.2022 Marine 2T Motor Oil

Wash hands before breaks and at end of work. Keep away from food, drink and animal feedingstuffs. Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles (EN 166) with side protection, with danger of splashes.

Skin protection - Hand protection: Protective nitrile gloves (EN ISO 374). Minimum layer thickness in mm: >= 0,4 Permeation time (penetration time) in minutes: >= 480 The breaktbrough times determined in accordance

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Protective hand cream recommended.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: If OES or MEL is exceeded. Filter A P2 (EN 14387), code colour brown, white Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

ആ

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

## 8.2.3 Environmental exposure controls

No information available at present.

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

3.1 millionnation on basic physical and chemi	
Physical state:	Liquid
Colour:	Red
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	Flammable
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	104 °C
Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	57,0 mm2/s (40°C)
Kinematic viscosity:	9,3 mm2/s (100°C)
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	0,870 g/cm3
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.



Page 6 of 13

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.04.2022 / 0017 Replacing version dated / version: 25.01.2022 / 0016 Valid from: 01.04.2022 PDF print date: 23.05.2022 Marine 2T Motor Oil

## 9.2 Other information

Explosives: Oxidising liquids: Product is not explosive.

## **SECTION 10: Stability and reactivity**

#### **10.1 Reactivity**

The product has not been tested.

**10.2 Chemical stability** Stable with proper storage and handling.

## 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Protect from humidity.

Open flame, ignition sources

#### **10.5 Incompatible materials** Avoid contact with strong oxidizing agents.

Avoid contact with strong oxidizing ager Avoid contact with other chemicals.

## **10.6 Hazardous decomposition products**

No decomposition when used as directed.

# **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Marine 2T Motor Oil							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	-					n.d.a.	
Acute toxicity, by dermal route:						n.d.a.	
Acute toxicity, by inhalation:						n.d.a.	
Skin corrosion/irritation:						n.d.a.	
Serious eye damage/irritation:						n.d.a.	
Respiratory or skin						n.d.a.	
sensitisation:							
Germ cell mutagenicity:						n.d.a.	
Carcinogenicity:						n.d.a.	
Reproductive toxicity:						n.d.a.	
Specific target organ toxicity -						n.d.a.	
single exposure (STOT-SE):							
Specific target organ toxicity -						n.d.a.	
repeated exposure (STOT-RE):							
Aspiration hazard:						n.d.a.	
Symptoms:						n.d.a.	

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics Toxicity / effect Endpoint Value Organism Test method Notes Unit Acute toxicity, by oral route: LD50 >5000 mg/kg Rat OECD 401 (Acute Oral Toxicity) Acute toxicity, by dermal route: LD50 >5000 mg/kg Rabbit OECD 402 (Acute Dermal Toxicity) LC50 >5000 mg/m3/8h Rat OECD 403 (Acute Acute toxicity, by inhalation: Vapours Inhalation Toxicity) Skin corrosion/irritation: OECD 404 (Acute Analogous Dermal conclusion, Irritation/Corrosion) Drying of the skin., Dermatitis (skin inflammation)



Page 7 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.04.2022 / 0017 Replacing version dated / version: 25.01.2022 / 0016 Valid from: 01.04.2022 PDF print date: 23.05.2022 Marine 2T Motor Oil

œ.

Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Analogous conclusion, Slightly irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:				Mouse	in vivo	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Analogous conclusion, Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Analogous conclusion, Negative
Specific target organ toxicity - single exposure (STOT-SE):						Analogous conclusion, No indications of such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	>=1000	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Aspiration hazard:						Yes
Symptoms:						drying of the skin., headaches, fatigue, dizziness, nausea, diarrhoea, vomiting

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute	
					Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant,
					Dermal	Repeated
					Irritation/Corrosion)	exposure may
						cause skin
						dryness or
						cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)
sensitisation:					Sensitisation)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative,
				typhimurium	Reverse Mutation Test)	Analogous
						conclusion



Page 8 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.04.2022 / 0017 Replacing version dated / version: 25.01.2022 / 0016 Valid from: 01.04.2022 PDF print date: 23.05.2022 Marine 2T Motor Oil

œ)

Germ cell mutagenicity:		OECD 473 (In Vitro	Negative,
		Mammalian	Analogous
		Chromosome	conclusion
		Aberration Test)	Chinese hamste
Germ cell mutagenicity:	Mouse	OECD 476 (In Vitro	Negative,
		Mammalian Cell Gene	Analogous
		Mutation Test)	conclusion
Germ cell mutagenicity:	Mouse	OECD 474 (Mammalian	Negative,
		Erythrocyte	Analogous
		Micronucleus Test)	conclusion
Carcinogenicity:		OECD 453 (Combined	Negative
		Chronic	•
		Toxicity/Carcinogenicity	
		Studies)	
Carcinogenicity:	Mouse	OECD 451	Negative,
		(Carcinogenicity Studies)	Analogous
		(	conclusion
Reproductive toxicity:		OECD 414 (Prenatal	Negative
.,		Developmental Toxicity	- 5
		Study)	
Reproductive toxicity:		OECD 421	Negative
		(Reproduction/Developm	lioguiro
		ental Toxicity Screening	
		Test)	
Reproductive toxicity:	Rat	OECD 421	Negative,
	, in the second s	(Reproduction/Developm	Analogous
		ental Toxicity Screening	conclusion
		Test)	conclusion
Specific target organ toxicity -		OECD 453 (Combined	Negative
repeated exposure (STOT-RE):		Chronic	Negative
repeated exposure (STOT-RE).		Toxicity/Carcinogenicity	
		Studies)	
Specific target organ toxicity -		OECD 408 (Repeated	Negative
repeated exposure (STOT-RE):		Dose 90-Day Oral	Negative
repeated exposure (STOT-RE).			
		Toxicity Study in Rodents)	
Specific torget orgen tovicity			Negotivo
Specific target organ toxicity -		OECD 410 (Repeated	Negative
repeated exposure (STOT-RE):		Dose Dermal Toxicity -	
One sifis target argen tavisity		90-Day)	Negethie
Specific target organ toxicity -		OECD 411 (Subchronic	Negative
repeated exposure (STOT-RE):		Dermal Toxicity - 90-day	
		Study)	N I a start from
Specific target organ toxicity -		OECD 412 (Subacute	Negative
repeated exposure (STOT-RE):		Inhalation Toxicity - 28-	
		Day Study)	· - ·
Aspiration hazard:			Asp. Tox. 1

# 11.2. Information on other hazards

Marine 2T Motor Oil						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

# **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).



Page 9 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.04.2022 / 0017 Replacing version dated / version: 25.01.2022 / 0016 Valid from: 01.04.2022 PDF print date: 23.05.2022 Marine 2T Motor Oil

œ.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							Mechanical
degradability:							precipitation possible.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.
12.7. Other adverse							No information
effects:							available on
							other adverse
							effects on the
							environment.
Other information:							DOC-eliminatio
							degree(comple
							ng organic
							substance)>=
							80%/28d: No

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Water solubility:							Insoluble
12.1. Toxicity to fish:	NOELR	28d	0,17	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	NOELR	21d	1,22	mg/l	Daphnia magna	QSAR	
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	NOELR	72h	1000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	69	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		6-8			· · · · · · · · · · · · · · · · · · ·	High
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based							
Endpoint	Time	Value	Unit	Organism	Test method	Notes	
NOEC/NOEL	10min	> 1,93	mg/l	activated sludge		DIN 38412	
NOEC/NOEL	96h	>=100	mg/l	Pimephales	OECD 203 (Fish,		
				promelas	Acute Toxicity		
					Test)		
LL50	96h	> 100	mg/l	Pimephales	OECD 203 (Fish,		
			_	promelas	Acute Toxicity		
					Test)		
	Endpoint NOEC/NOEL NOEC/NOEL	Endpoint Time NOEC/NOEL 10min NOEC/NOEL 96h	EndpointTimeValueNOEC/NOEL10min> 1,93NOEC/NOEL96h>=100	EndpointTimeValueUnitNOEC/NOEL10min> 1,93mg/lNOEC/NOEL96h>=100mg/l	EndpointTimeValueUnitOrganismNOEC/NOEL10min> 1,93mg/lactivated sludgeNOEC/NOEL96h>=100mg/lPimephales promelasLL5096h> 100mg/lPimephales	EndpointTimeValueUnitOrganismTest methodNOEC/NOEL10min> 1,93mg/lactivated sludgeNOEC/NOEL96h>=100mg/lPimephales promelasOECD 203 (Fish, Acute Toxicity Test)LL5096h> 100mg/lPimephales promelasOECD 203 (Fish, Acute Toxicity Test)	



Page 10 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.04.2022 / 0017 Replacing version dated / version: 25.01.2022 / 0016 Valid from: 01.04.2022 PDF print date: 23.05.2022 Marine 2T Motor Oil

œ

12.1. Toxicity to daphnia:	EL50	48h	>10000	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	OECD 211	
				_		(Daphnia magna	
						Reproduction Test)	
2.1. Toxicity to algae:	NOEC/NOEL	72h	>=100	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
, 0				Ū	a subcapitata	Growth Inhibition	
						Test)	
2.1. Toxicity to algae:	EL50	48h	>100	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
, 0				Ū	a subcapitata	Growth Inhibition	
						Test)	
2.2. Persistence and						OECD 301 B	Not readily
legradability:						(Ready	biodegradable
0						Biodegradability -	Ū
						Co2 Evolution	
						Test)	
2.2. Persistence and		28d	46	%		OECD 301 B	
legradability:						(Ready	
,						Biodegradability -	
						Co2 Evolution	
						Test)	
2.3. Bioaccumulative	Log Kow		>6				A notable
otential:	-						biological
							accumulation
							potential has to
							be expected
							(LogPow > 3).
2.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

## **SECTION 13: Disposal considerations**

# 13.1 Waste treatment methods

## For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

07 06 99 wastes not otherwise specified

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

15 01 01 paper and cardboard packaging 15 01 02 plastic packaging

15 01 02 plastic packaging 15 01 04 metallic packaging

# **SECTION 14: Transport information**

# **General statements**

14.1. UN number or ID number:



Page 11 of 13

(GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.04.2022 / 0017 Replacing version dated / version: 25.01.2022 / 0016 Valid from: 01.04.2022 PDF print date: 23.05.2022 Marine 2T Motor Oil

## Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Classification code:	n.a.
LQ:	n.a.
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	
Transport by sea (IMDG-code)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Marine Pollutant:	n.a
14.5. Environmental hazards:	Not applicable
Transport by air (IATA)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
14.5. Environmental hazards:	Not applicable
14.6. Special precautions for user	
Unless specified otherwise, general measures for safe transport	t must be followed.
14.7 Maritima transport in bulk apparding t	MO instruments

14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

#### **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions: General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): Directive 2010/75/EU (VOC): 22,7 % 197,5 g/l

#### **15.2 Chemical safety assessment**

A chemical safety assessment is not provided for mixtures.

**SECTION 16: Other information** 

Revised sections:

2

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3). H304 May be fatal if swallowed and enters airways.

EUH066 Repeated exposure may cause skin dryness or cracking.

Asp. Tox. — Aspiration hazard

## Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended. Guidelines for the preparation of safety data sheets as amended (ECHA). Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA). Safety data sheets for the constituent substances. ECHA Homepage - Information about chemicals. GESTIS Substance Database (Germany).



Page 12 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.04.2022 / 0017 Replacing version dated / version: 25.01.2022 / 0016 Valid from: 01.04.2022 PDF print date: 23.05.2022 Marine 2T Motor Oil

ആ

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany). EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended. Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

## Any abbreviations and acronyms used in this document:

according, according to acc., acc. to ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF **Bioconcentration factor** BSEF The International Bromine Council bw body weight CAS **Chemical Abstracts Service** CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) carcinogenic, mutagenic, reproductive toxic CMR DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.q. EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) European Community EC ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect EEC European Economic Community European Inventory of Existing Commercial Chemical Substances EINECS European List of Notified Chemical Substances FI INCS EN European Norms EPA United States Environmental Protection Agency (United States of America)  $ErCx, E\mu Cx, ErLx (x = 10, 50)$ Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) etc. et cetera EU **European Union** EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number general aen. GHS Globally Harmonized System of Classification and Labelling of Chemicals Global warming potential GWP Adsorption coefficient of organic carbon in the soil Koc octanol-water partition coefficient Kow IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Logarithm of adsorption coefficient of organic carbon in the soil Log Koc Log Kow, Log Pow Logarithm of octanol-water partition coefficient Limited Quantities 10 MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a.



ആ Page 13 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.04.2022 / 0017 Replacing version dated / version: 25.01.2022 / 0016 Valid from: 01.04.2022 PDF print date: 23.05.2022 Marine 2T Motor Oil n.av. not available n.c. not checked n.d.a. no data available NIOSH National Institute for Occupational Safety and Health (USA) NLP No-longer-Polymer NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development ora. organic OSHA Occupational Safety and Health Administration (USA) PBT persistent, bioaccumulative and toxic ΡE Polyethylene PNEC Predicted No Effect Concentration parts per million ppm PVC Polyvinylchloride REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List REACH-IT List-No. Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International RID Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Tel. Telephone TOC Total organic carbon UN RTDG United Nations Recommendations on the Transport of Dangerous Goods VOC Volatile organic compounds very persistent and very bioaccumulative vPvB wet weight wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

#### These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.